

Declaration of Performance

according to Annex III of the Regulation (EU) No. 305/2011
(Construction Products Regulation)

Mulcol® Multifoam Stone

No. M2KS-ST 0761-CPR-0804

1. Unique identification code of the product-type:

Mulcol® Multifoam Stone

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

See batch number on the packaging of the product.

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

3.1 The intended use of the system Mulcol® Multifoam Stone is to reinstate the fire resistance performance of penetrations in walls and floors, as included in ETA 17/0977 and ETA 17/0831.

3.2 The conditions under which the system Mulcol® Multifoam Stone can be used are intended for indoor use, conditions: relative humidity $\geq$ than 85% RH, excluding temperatures below 0 °C, and without exposure to rain or UV (TR 024: 2019, model Z₁).

3.3 The provisions made in the ETA 17/0831 are based on an assumed working life of the Mulcol® Multifoam Stone for 30 years, provided that the conditions laid down in the manufacturer's datasheet and instructions for the packaging, transport, storage, installation, use and repair are met.

The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Mulcol International
Promenade 75
5401 GM Uden
The Netherlands

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

AVCP-System 1

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Not applicable

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

This Declaration of Performance has been prepared in accordance with the guidelines set out within EAD 350454-00-1104. ETA 17/0977 and ETA 17/0831 are prepared by MPA Braunschweig notified body 0761 and has issued EC Certificate of Conformity 0761-CPR-0804.

9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to Fire	E	EN 13501-1
Resistance to Fire	Classified as construction product or construction set to a resistance to fire classification EI 120 depending on local parameters and the execution. For details, see ETA 17/0977 & ETA 17/0831	EN 13501-2
Durability and serviceability	Z ₁ according TR 024:2019	ETAG 026-2

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Ing. W. Scheffer-Geuze
Technical Director

